

TwistPort™ Adaptor for ePMP

ADAPTOR FOR EPMP™ 1000 AND 3000

The TwistPort™ Adaptor for ePMP™ 1000 AP and CSM, ePMP™ 3000L AP and ePMP™ Force 300 CSM series, PMP 450b is compatible with all TwistPort™ Antennas. TwistPort™ Adaptors are equipped with our original quick-locking waveguide connector with near zero loss.

Connecting and disconnecting the radio into the TwistPort™ Adaptor is very simple and requires no tools.



TECHNICAL DATA

Antenna Connection	TwistPort™ - Quick Locking Waveguide Port
Radio Connection	2x Slide-On RP-SMA
Materials	Insert - Aluminium Alloy Adaptor - UV stabilized and weather resistant ABS plastic
Flame Rating	UL 94 HB
Temperature	-40°C to +60°C (-40°F to +140°F)
Wind Survival	160 km/h (100 miles/h)
Weight	0.4 Kg (0.9 lbs) – single unit 0.5 Kg (1.1 lbs) – single unit incl. package 11.2 Kg (24.7 lbs) – carton (20 units)
Single Unit	Retail Box: 130 x 120 x 135 mm (5.1 x 4.7 x 5.3 inch)
20 Units	Carton Box: 295 x 280 x 610mm (11.6 x 11 x 24 inch)

PERFORMANCE

Frequency Range	5180 - 6400 MHz
Polarization	Dual Linear H + V
VSWR Max	1.8
Impedance	50 Ohm

COMPATIBLE WIRELESS PLATFORMS

RF elements®	any TwistPort™ Antenna
Cambium Networks™	ePMP™ 1000 AP, ePMP™ 1000 CSM, ePMP™ 3000L AP, ePMP™ Force 300 CSM, PMP 450b Connectorized SM

PACKAGE CONTENTS

TwistPort™ Adaptor

PRODUCT DIMENSIONS

